



C900

PipeLife Jet Stream manufactures the AWWA C900 product family which includes 4" to 12" C.I OD pipes. AWWA C900 standards include all specifications relating to the production and testing of C900 pipes. In three pressure ratings of DR 14, DR 18 and DR 25.

Our C900 is suitable for the transmission and distribution of water. PipeLife Jet Stream carries various certifications from NSF International (NSF), Underwriters Laboratories (UL) and Factory Mutual (FM).

PipeLife Jet Stream uses compound according to ASTM D1784—12454 as well as integral gasket joints according to ASTM F477 and ASTM D3139. To aid in the installation of PipeLife Jetstream's C900, each spigot end is beveled and includes a depth mark for insertion



DR 14 Pressure Ratings are: **UL 305 PSI** and **FM 200 PSI** both at 73.4 degrees

Size	Outside Diameter	Minimum Wall Thickness	Weight LBS/Foot	Pieces per Pallet	Order Units
4	4.80	.343	3.22	36	2.4
6	6.90	.493	6.70	18	2.4
8	9.05	.646	11.55	10	2.4
10	11.10	.793	17.46	4	1.71
12	13.20	.943	24.75	4/3	4

DR 18 Pressure Ratings are: **UL 235 PSI** and **FM 150 PSI** both at 73.4 degrees

Size	Outside Diameter	Minimum Wall Thickness	Weight LBS/Foot	Pieces per Pallet	Order Units
4	4.80	.267	2.55	36	2.4
6	6.90	.383	5.29	18	2.4
8	9.05	.503	9.15	10	2.4
10	11.10	.617	13.82	4	1.71
12	13.20	.733	19.56	4/3	4

DR 25 Pressure Rating: **UL 165 PSI** at 73.4 degrees

Size	Outside Diameter	Minimum Wall Thickness	Weight LBS/Foot	Pieces per Pallet	Order Units
4	4.80	.192	1.87	36	2.4
6	6.90	.276	3.90	18	2.4
8	9.05	.362	6.69	10	2.4
10	11.10	.444	10.16	4	1.71
12	13.20	.528	14.43	4	4

** All PipeLife Jet Stream C900 products are available in optional colors**